Ameron™ Victorian III Pole

Available in base plate and embedded styles.

Eight crisp, sharp flowing lines, a flared base and the tapered shaft are reminiscent of the gas lamp era. Victorian III works well with traditional and contemporary architectural designs.

Our Victorian Series lighting poles combine the charm of yesterday with the technology of today. Available in a variety of configurations, colors and finishes, the Victorian series provides architects and designers with many creative options.

Features and Benefits

- Prestressed steel and highest quality concrete are centrifugally cast for ultimate strength and long-term durability
- Natural stone and terrazzo aggregates maintain a like new appearance with virtually no maintenance
- Conforms to applicable sections of ACI, AASHTO, ASTM and PCI standards
- Exclusive 10-year warranty

Colors and Finishes

A wide range of standard, pre-formulated and custom colors are available. The concrete shafts are lightly blasted to expose the texture and beauty of the natural stone. See separate Aggregates and Finishes sheet for details. We offer Amershield™, a premium graffiti-resistant coating, as well as other durable sealers and protectants that further enhance colors, protect the concrete surface and aid in the removal of graffiti.

Durability with a classic touch.





Top OD across the flats

"A"

Base plate style - information

Catalog Number	Pole Height	Top OD	Base OD	Anchor Bolt	Bolt Circle	Base Plate (Sq)	Ultimate G.L. Moment (ft. lbs.)	Pole Weight (lbs.)
VBO03.0	9'-10"	71/2"	18"	3/4" x 24" x 4"	21"	20"	22,500	720
VBO03.7	12'-2"	71/2"	18"	3/4" x 24" x 4"	21"	20"	22,500	875
VBO04.5	14'-9"	71/2"	18"	3/4" x 24" x 4"	21"	20"	22,500	1,000
VBO04.8	15'-9"	63/4"	18"	3/4" x 24" x 4"	21"	20"	22,500	1,100
VBO05.5	18'-0"	6¾"	18"	3/4" x 24" x 4"	21"	20"	22,500	1,300
VBO06.3	20'-8"	6¾"	18"	3/4" x 24" x 4"	21"	20"	22,500	1,400
VBO09.0	29'-6"	51/8"	18"	3/4" x 24" x 4"	21"	20"	22,500	1,850
VBOX10.5	34'-6"	51/8"	18"	3/4" x 24" x 4"	21"	20"	32,000	2,200

Embedded style - information

Catalog Number	Pole Height "A"	Top OD	Base OD	Embedded Depth "B"	Overall Length	Ultimate G.L. Moment (ft. lbs.)	Pole Weight (lbs.)
VEO03.0	9'-10"	7½"	18"	5'-0"	14'-10"	22,500	900
VEO03.7	12'-2"	71/2"	18"	5'-0"	17'-2"	22,500	1,050
VEO04.5	14'-9"	7½"	18"	5'-0"	19'-9"	22,500	1,100
VEO04.8	15'-9"	63/4"	18"	5'-0"	20'-9"	22,500	1,200
VEO05.5	18'-0"	6¾"	18"	5'-0"	23'-0"	22,500	1,450
VEO06.3	20'-8"	6¾"	18"	5'-0"	25'-8"	22,500	1,500
VEO09.0	29'-6"	51/8"	18"	5'-0"	34'-6"	22,500	2,000
VEOX10.5	34'-6"	51/8"	18"	5'-0"	39'-6"	32,000	2,300

"OL" **Specifications:** Use Centrecon Specifications Colors and finishes: See Centrecon color selection guide **Luminaire mounting:** See Mounting Options section for more information Anti-graffiti and sealer: Optional coatings are available for added protection Ground 39" Base Line PC Wires 18" Double cable "B" entrances Slotted base plate Elevation Shaft cross See recommended prestressed to pole section detail "capping detail"

For further information contact us at: 1.800.552.6376

