

# Sub-Sea Umbilical Reelers

The Elmar 'Reel Pack' hose tensioning units cover a large range of umbilical diameters and lengths. All units have the standard safety feature of a self-centering directional control hand lever, which has to be used in conjunction with the 'Dead Mans' foot pedal to facilitate drum rotation.

These units can be manufactured to DNV 2.7-1 or the latest BS EN 12079 specifications. Custom units built on request.

The Reel Pack featured is designed to accept a one core Umbilical of 3.600m (11,811ft) in length with a minimum bend radius of 850mm.



Part Number L-6941057373



## Dimensions & Weights

PART NUMBER L-6941057373

(L) 2.98 m, 9.78 ft (W) 2.52 m, 8.27 ft (H) 2.57 m, 8.43 ft (Weight) 9,000 kg, 19,842 lbs

## Specifications


Core Dia:	850mm
Capacity (28mm hose):	3,600m
Max. Drum Speed:	7rpm
Max. Line Speed:	124ft/min
Max. Line Pull (Running):	650kg

## Features & Benefits

- CE marked, ATEX approved
- DNV 2.7-1/BS EN12079 certified frame
- Pneumatic driven manual spooler
- Guards on all moving parts
- Integral fork lift pockets

## Options

- Multiway hydraulic/electric slip rings
- Auto tensioning
- Auto spooler



Chain guard

## Dimensions & Weights

PART NUMBER L-6941064626

(L) 4.00 m, 13.12 ft (W) 3.00 m, 9.84 ft  
(H) 4.00 m, 13.12 ft (Weight) 23,000 kg, 50,706 lbs

## Specifications

Core Dia:	1,340mm
Capacity (64mm hose):	3,400m
Max. Drum Speed:	3rpm
Max. Line Speed:	60ft/min

## Features & Benefits

- CE marked ATEX
- DNV 2.7-1
- Pneumatic driven
- Auto spooler with correction facility
- Guards
- Integral forklift
- 30 channel electrical slip ring
- 6 channel 15000 PSI hydraulic slip ring
- Remote control station.
- Auto tensioning
- Disc brake
- -20°C to +50°C

## Dimensions & Weights (approx.)

PART NUMBER L-6941064627

(L) 2.98 m, 9.78 ft (W) 2.50 m, 8.20 ft  
(H) 2.57 m, 8.43 ft (Weight) 5,000 kg, 11,023 lbs

## Specifications

Core Dia:	1,150mm
Capacity (58mm hose):	300m (TBC)
Max. Drum Speed:	3rpm
Max. Line Speed:	60ft/min

## Features & Benefits

- CE marked ATEX
- DNV 2.7-1
- NORSOK
- Pneumatic driven
- Guards
- Integral forklift
- 6 channel 15000 PSI hydraulic slip ring
- Remote control station.
- Auto tensioning
- Disk brake
- -20°C to +50°C