

## Steel Pickling Line (Hot HCl)



**Application:** Hot hydrochloric acid is used to “pickle” steel to remove iron oxide scale that is formed during the processing of semi-finished steel. Typical operating conditions are 18-20% HCl solution at 190°F/88°C.

**Location:** Cleveland, Ohio

**Product:** Approximately 3,800 feet of Centricast® RB epoxy cast pipe and 1,200 fittings in diameters 1.5”-10”

**Features & Benefits:** The customer chose the RB product after a detailed investigation of various piping materials. Their decision was based on RB’s robust construction (including 100 mil corrosion barrier), ease of installation, superior support spans and availability of one-piece molded flanged fittings. Technical installation and product support from the local FGS distributor was another plus in the decision. The fabricator/installer on this project was FGS ASME B31.3 bonder certified resulting in a smooth installation.

*North America*  
17115 San Pedro Ave. Suite 200  
San Antonio, Texas 78232 USA  
Phone: 210 477 7500

*South America*  
Avenida Fernando Simoes  
Recife, Brazil 51020-390  
Phone: 55 31 3501 0023

*Europe*  
P.O. Box 6, 4190 CA  
Geldermalsen, The Netherlands  
Phone: 31 345 587 587

*Asia Pacific*  
No. 7A, Tuas Avenue 3  
Jurong, Singapore 639407  
Phone: 65 6861 6118

*Middle East*  
P.O. Box 17324  
Dubai, UAE  
Phone: 971 4881 3566