

Production Wells - Stinnett, Texas



Application: Production Well - 2009

Location: Kador F-1 & D-4 Field
Stinnett, Texas USA (Linn Energy LLC)

Product: 2 3/8", 3000 psi Aliphatic Amine Downhole Tubing

Operating Pressure: 150 psi (1,0 MPa)

Operating Temperature: Ambient

Joining System: Integral Joint (IJ)

Quantity: 3100 feet (945 meters)
3237 feet (986 meters)

Product Conditions: 60 HP Submersible Pump moving approximately 300 bpd.



North America
2425 SW 36th Street
San Antonio, Texas 78237 USA
Phone: 210 434 5043

South America
Avenida Fernando Simoes
Recife, Brazil 51020-390
Phone: 55 31 3501 0023

Europe
P.O. Box 6, 4190 CA
Geldermalsen, The Netherlands
Phone: 31 345 587 587

Asia Pacific
No. 7A, Tuas Avenue 3
Jurong, Singapore 639407
Phone: 65 6861 6118

Middle East
P.O. Box 17324
Dubai, UAE
Phone: 971 4881 3566

www.fgspipe.com • fgspipe@nov.com

 **Fiber Glass Systems**

© 2012 National Oilwell Varco. All rights reserved.
CH2011 February 2008