

TerraLINK Coiled Tubing Connectors



Our TerraLINK™ slip-type coiled tubing connector is the solution for reliable performance in applications that generate high torsional and tensile loads. Developed with the latest material technologies and extensively tested to ensure world-class reliability in the world’s most demanding applications. The rugged design of the TerraLINK connector helps reduce the overall cost of ownership through improved wear resistance of its components.

Available with a wide variety of ODs and pin connections to accommodate most jobs without the need for crossovers.

Part no.	CT size	Tool OD	Tool ID	Service	Connection	Pressure rating	Service kit*
621-350	1¼"	1½⅙"	0.750"	Standard	1" AMMT	10 KPSI	621-350-RDK
621-400	1¼"	1½⅙"	0.750"	Sour	1" AMMT	10 KPSI	621-350-RDK
622-350	1½"	2⅙"	1.000"	Standard	1½" AMMT	10 KPSI	622-350-RDK
622-550	1½"	2⅙"	1.000"	Sour	1½" AMMT	10 KPSI	622-350-RDK
623-300	1¾"	2⅞"	1.000"	Standard	1½" AMMT	10 KPSI	623-300-RDK
623-350	1¾"	2⅞"	1.000"	Sour	1½" AMMT	10 KPSI	623-300-RDK
634-300	2"	2⅞"	1.375"	Standard	2⅞" PAC	10 KPSI	634-300-RDK
634-500	2"	2⅞"	1.375"	Sour	2⅞" PAC	10 KPSI	634-300-RDK
635-350	2⅝"	3⅞"	1.000"	Standard	2⅝" REG	10 KPSI	635-350-RDK
635-450	2⅝"	3⅞"	1.000"	Sour	2⅝" REG	10 KPSI	635-350-RDK
636-250	2⅝"	3½"	1.000"	Standard	2⅝" REG	10 KPSI	636-250-RDK
636-300	2⅝"	3½"	1.000"	Sour	2⅝" REG	10 KPSI	636-250-RDK

*Includes Slip